

## **MACRODUCT® ADVANCED**

**Sweat Induction and Collection** 

**STANDARD** 





## WORLD LEADER IN LABORATORY CF DIAGNOSIS

personnel for stimulation and collection of sweat from



### MACRODUCT® ADVANCED IS SWEAT TESTING AT ITS BEST

More than 5 million sweat tests have been performed with the existing Macroduct® Sweat Collection System. The Macroduct® Advanced is a result of 40+ years of ongoing innovation to further standardize pilocarpine iontophoresis and sweat collection.



- Elliptical shaped collector is a better fit for small arms
- Minimum amount of sweat needed is 15 microliters in a 30-minute collection period
- Two marks on each collector for checking the minimum volume of sweat required and determining the sweat rate

# Adjustable and Disposable Straps

Easy to fit and disinfect for reuse



Easyduct® Needle has a tapered blunt end for easy insertion into the tubing and transferring sweat



# THE CHLOROCHEK® CHLORIDOMETER® THE PERFECT CF DIAGNOSTIC COMPANION

The ChloroChek® Chloridometer® is a coulometric titrator designed to determine chloride ion concentrations in sweat samples with just 10 microliters of sweat. It displays the concentration directly in mmol/L Cl-. The sweat sample is added to a buffer/stabilizer working solution.



### **Key Advantages**

- Easy to operate with consistent results in less than 20 seconds
- Intuitive touchscreen interface with simple prompts
- Maintenance for electrodes is simple

   a daily rinse with deionized water
- Electrodes are simply pushed into place
- Results can be exported for complete traceability





SWEAT CONTROLS ARE AVAILABLE, WITH THREE LEVELS, TO INSURE THE HIGHEST QUALITY CONTROL PROCEDURES TO MEET REGULATORY REQUIREMENTS





### Macroduct Advanced® Sweat Collection System Model 3710

\*Includes all needed accessories and one supply kit. Each kit contains 12 Macroduct Advanced Pilogel discs, 6 Macroduct Advanced collectors, and 6 small sealable containers.

Iontophoresis Current (nominal control)	(a) Current profile-controlled ramp-up and ramp-down	
	(b) 1.5 mA	
	(c) Fail-safe current limited by circuit design	
Electrode Cable Assembly	Color-coded elliptically shaped electrodes to fit elliptical Pilogel discs	
USB Connection	Micro USB connector for exporting test data	
Power	Rechargeable lithium ion battery	
Device & Carrying Case Weight	5 lbs (2.3 kg)	

### ChloroChek® Chloridometer® Model 3400

Sample Volume	10 μL		
Duration of Measurement	Approximately 20 Seconds		
Reproducibility (*Generally limited by the sample dispensing system/pipette accuracy)	CV of 1.02% at 100 mmol/L		
Measurement Display	0 - 999 mmol/L		
Clinical Measuring Range	10 - 160 mmol/L		
Resolution	1 mmol/L over the entire measurement range		
Integrated Stir Bar	PTFE coated magnetic cylindrical stir bar		
Environmental Operating Conditions	Indoor use; no direct sunlight		
Operating Temperature (ambient)	10 °C to 35 °C / 50 °F to 95 °F		
Storage Temperature	-40 °C to 70 °C / -40 °F to 158 °F		
Room Humidity	5 - 80% (non-condensing)		
Altitude	Up to 2000 m		
Electrical Voltage	100 -120 VAC / 200 - 240 VAC		
Frequency	50 - 60 Hz		
Power	20 VA		
Electrical Connection	Detachable power supply cord		
Fuses (2): HBC breaking capacity 1500 A	1.0 A for 100-120 VAC		
	0.5 A for 200-240 VAC		
Memory Backup	Integral lithium cell: (10 years typical)		
Dimensions: (W x D x H)	20.5 x 22.0 x 36.0 cm (8.0 x 8.1 x 14.2 inches)		
Weight	Approximately 5.7 kg (12.54 lbs.)		
Data Output	Serial RS-232 / USB		

	Catalog Number	Description		Catalog Number	Description
	MODEL 3710-SYS	Macroduct® Advanced 3710 Sweat Collection System	Chek	MODEL 3400	ChloroChek® Chloridometer® Sweat Chloride Analyzer
_	AC-193	EasyDuct Needle/1cc Syringe, Pack of 3		AC-071	Ampule Organizer for Sweat Controls
ced	RP-537 Electrode Cable Assembly Macroduct® Advanced	Electrode Cable Assembly Macroduct®	loro	SS-150	Sweat Controls, L1, L2, L3 12 ea., 36x0.75mL
van		ਨ	SS-248	ChloroChek® Reagent Set, 37x10mL BS + 1x30mL GS	
Ad	SS-107	Small Sealable Containers, Pack of 6		SS-251	ChloroChek® Standard Solution, 100 mmol/L, 10x1mL
uct	SS-268	Macroduct® Advanced Supply Kit			
Macrod	SS-268-ND	Macroduct® Advanced Supply Kit, No Dye Collectors			
2	SS-269	Strap Set, 18 ea, Macroduct® Advanced			
	SS-270	Strap Set, 180 ea, Macroduct® Advanced			
	SS-271	Electrode Cleaning Pads, Pack of 10			



### **WORLDWIDE OFFICES**

Please contact your sales representative for terms, conditions and product availability in your country.



ELITechGroup has been certified by BSI to ISO 13485:2016 under certificate numbers MDSAP 689350 and FM 703046



Headquarters +33 1 41 45 07 10 Australia T: +61 1800 815 098 Belgium & Luxembourg T: +32 9 282 05 31 T: +55 27 3025 1415 Brazil T: +33 4 83 36 10 82 France Italy T: +39 02 48 40 35 42 New Zealand T: +64 800 555 611

Canada Serbia Switzerland

T: +1 888 662 4925 T: +381 11 2467119 T: +41 26 663 86 60 T: +31 313 430 500 The Netherlands T: +44 1442 869320 United States T: +1 435 752 6011

